
## UNIVERSITY OF MICHIGAN

## ART + ARCHITECTURE BUILDING ADDITION


Location: Ann Arbor, Michigan Space Type: Academic/Office Total Square Footage: 15,782 sf


The Art + Architecture Building Addition project will add new office and academic spaces to the growing Taubman College of Architecture + Urban Planning at the University of Michigan. Taking up no new site area, the addition will be built atop the existing structure in an environmentally-ideal location where it is envisioned to help prepare students for a future increasingly involved in sustainable design. A glassy south façade and kinetic sun shade veil will perform as an efficient passive solar "engine" in cold winters and hot summers, and will broadcast the college's active design studio culture to the University and community beyond.





71.6 kBtu/sf/year (site EUI) 152.6 kBtu/sf/year (source EUI) 46% CO<sub>2</sub> production reduction 90 Energy Star rating 2,049,772.7 kBtu/year Energy savings 168 tons/year CO<sub>2</sub> savings \$1.20 annual energy cost/sf





Clerestory windows open automatically Light signals occupants to open floor-level windows Outside air drawn in at night to cool building mass

Low-Emitting

Double pane insulated Low-E glazing

92% efficient condensing boiler dual flush toilets ultra-low flow urinals hands-free, PV-powered faucets





The Miller Hull Partnership - Seattle, WA PAE Consulting Engineers - Portland, OR



he estimated energy erformance for this design meets US EPA criteria. The building will be eligible for ENERGY STAR after

## SUSTAINABLE STRATEGIES

SUSTAINABLE SITING

Building on top of existing building Reduce heat loss of existing building Shade existing building with new overhang No net increase of impervious surface Ideal orientation Passive Solar

Daylighting Ventilation

DAYLIGHTING

solstice

No electric lighting required during the day Translucent skylights North-facing clerestories and windows South-facing glazing with glare control

PASSIVE SOLAR STRATEGIES Motorized exterior louver shades block/direct light

> Manually-operated interior roll-down shades Concrete slab floor store energy and reradiate heat Transpired air collector (winter only) Sun heats perforated metal siding Siding warms air layer between brick wall and siding

Pre-heated air drawn into HVAC system

DISPLACEMENT HEATING/COOLING

Fresh air supplied low and stale air returned high Manually-operated VAV floor-diffusers allow individual control

RADIANT HEAT

Hot water radiant slab @ crit space Hot water finned tube radiators @ offices/perimeter

NATURAL VENTILATION

Under favorable conditions: HVAC system automatically shuts off

**GREEN MATERIALS** 

Recycled content Salvaged and Reused

**EXTRA INSULATION** 

Exceeds code by R-7.5 at walls and R-8 at roof

EFFICIENT EQUIPMENT